

Impact wrenches - 1/2"

RediPower



RP9526

Very compact 1/2" tool

FEATURES

- Pin clutch
- Friction ring socket retainer
- Built in power regulator
- Through handle air exhaust
- Compact & ergonomic
- Forward position: 4 power settings
- Maximum reverse power

BENEFITS

- High torque in a compact tool
- One hand push button forward/reverse

RP9527



Same features as RP9526 with Pin socket retainer



RP9540-B

High torque/size ratio

FEATURES

- Pin clutch
- Friction ring socket retainer
- Through handle air exhaust
- Compact & ergonomic
- Forward position: 4 power settings
- Maximum reverse power

BENEFITS

- High torque/size ratio
- One hand push button forward/reverse

RP9550-B RP9552-B Kits



Same features as RP9540-B in kits with Imperial (IKIT) and Metric (MKIT) sockets sizes

See details on page 9



RP9541

Withstanding rough use

FEATURES

- Pin clutch in oil bath
- Friction ring socket retainer
- Steel clutch housing

BENEFITS

- Ideal for fast rundown with high torque
- Easy maintenance
- Durability

RP9542



Same features as RP9541 with Pin socket retainer

RP9543



Same features as RP9541 with Quick change chuck



RP9545

Durability & economy

FEATURES

- Pin clutch
- Friction ring socket retainer
- High reverse torque
- High torque/air consumption ratio
- Ergonomic handle

BENEFITS

- Ideal for rework operations
- Operator comfort
- Quick torque adjustment

See accessories on page 9

MODEL	PART NUMBER	SQUARE DRIVE	FREE SPEED	WORKING TORQUE		MAXIMUM TORQUE		AIR CONSUMPTION		OVERALL LENGTH		NET WEIGHT		NOISE LEVEL	SOUND POWER	VIBRATION	AIR INLET
		in.	rpm	Nm	ft lb	Nm	ft lb	l/s	cfm	mm	in.	kg	lb	dB(A)	dB(A)	m/s ²	NPTF
RP9526	615 190 9526	1/2	8,500	27-217	20-160	272	200	5.7	12	152	6.0	1.4	3.1	94	105	<2.5	1/4"
RP9527	615 190 9527	1/2	8,500	27-217	20-160	272	200	5.7	12	152	6.0	1.4	3.1	94	105	<2.5	1/4"
RP9540-B	615 190 2540	1/2	8,400	34-420	25-310	576	425	7.1	15	191	7.5	2.3	5.1	94	105	<2.5	1/4"
RP9541	615 190 9541	1/2	8,900	34-434	25-320	603	445	6.6	14	168	6.6	2.5	5.5	89	100	2.7	1/4"
RP9542	615 190 9542	1/2	8,900	34-434	25-320	603	445	6.6	14	168	6.6	2.5	5.5	89	100	2.7	1/4"
RP9543	615 190 9543	7/16 hex	8,900	34-434	25-320	603	445	6.6	14	199	7.8	2.6	5.8	89	100	2.7	1/4"
RP9545	615 190 9545	1/2	6,900	34-542	25-400	746	550	9.0	19	180	7.1	2.5	5.6	96	107	4.0	1/4"
RP9550-B IKIT	615 190 8550	1/2	8,400	34-420	25-310	576	425	7.1	15	191	7.5	2.3	5.1	94	105	<2.5	1/4"
RP9552-B MKIT	615 190 8552	1/2	8,400	34-420	25-310	576	425	7.1	15	191	7.5	2.3	5.1	94	105	<2.5	1/4"

@90 PSI(@6.3 Bar) - Listed specifications are for reference only. Please check documents in each tool.