

Impact wrenches - 1"

RediPower



MAGNESIUM

RP8084

Compact Size

FEATURES

- Twin dog clutch
- Hole type socket retainer
- High power: 1650 Nm
- 100% Magnesium housing
- Forward position: 3 power settings
- Cushion grip handle

BENEFITS

- Low noise
- Great durability and power
- Operator comfort



RP8085

Same features as RP8084 with an extended 152 mm (6") anvil



RP9597

Power & easy handling

FEATURES

- 2 Jaw clutch in oil bath
- Hole type socket retainer
- Steel clutch housing
- 3 pieces construction
- High torque

BENEFITS

- Good for both soft & hard joints
- Withstands rugged use
- Adjustable dead handle for operator comfort



RP9582

Safe & easy to handle

FEATURES

- Rocking dog clutch
- Hole and friction ring socket retainer
- Progressive throttle permits slow seating of bolt
- Inside trigger

BENEFITS

- Ideal for soft pull & prevailing torque joints
- Good handling & directional changes



RP9583

Easy access in tight areas

FEATURES

- Rocking dog clutch
- Friction ring socket retainer
- Progressive throttle permits slow seating of bolt
- 152mm (6") extended anvil
- Reverse valve

BENEFITS

- Ideal for soft pull & prevailing torque joints
- Good handling & directional changes
- Extended anvil for easy access

See accessories on page 9

MODEL	PART NUMBER	SQUARE DRIVE	FREE SPEED	WORKING TORQUE		MAXIMUM TORQUE		AIR CONSUMPTION		OVERALL LENGTH		NET WEIGHT		NOISE LEVEL	SOUND POWER	VIBRATION	AIR INLET
				Nm	ft lb	Nm	ft lb	l/s	cfm	mm	in.	kg	lb				
RP8084	615 190 8084	1	6,500	135-1300	100-960	1650	1217	17.0	36	230	9.05	5.05	11.13	94	105	9.0	3/8"
RP8085	615 190 8085	1	6,500	135-1300	100-960	1650	1217	17.0	36	387	15.2	5.92	13.0	94	105	9.0	3/8"
RP9582	615 190 9582	1	4,200	200-1225	150-900	1900	1400	18.9	40	394	15.5	12.3	27.0	110	121	4.3	1/2"
RP9583	615 190 9583	1	4,200	200-1225	150-900	1900	1400	18.9	40	564	22.2	13.5	29.8	110	121	4.3	1/2"
RP9597	615 190 9597	1	4,700	407-1898	300-1400	2712	2000	22.7	48	241	9.50	9.1	20.0	101	112	13.0	1/2"

@90 PSI(@6.3 Bar) - Listed specifications are for reference only. Please check documents in each tool.