

Sanders



RP9534

4-in-1 modular sander

FEATURES

- 3/16" (5mm) random orbital
- High quality "hook and loop" sanding pad
- Low vibration tool



3/16" (5mm) random orbital version for finishing sanding

BENEFITS

- Can be configured to suit application and operator
- Long lasting
- Ideal for fine finishing operations




RP9674

4-in-1 modular sander

FEATURES

- 3/8" (10mm) random orbital
- High quality "hook and loop" sanding pad
- Low vibration tool



3/8" (10mm) random orbital version for fast material removal


BENEFITS

- Can be configured to suit application and operator
- Long lasting
- Ideal for fast material removal




RP9164

General duty



or



3/8" (10mm) random orbital or rotary version, for finishing random, for fast material removal

FEATURES

- Rotary or random orbital options
- PSA sanding pad
- Sure-grip insulated handle
- Crossbolt-style hub mounting minimizes vibration

BENEFITS

- Ideal for multiple applications
- Ideal for fast material removal
- Operator comfort



RP9778

Fast and precise

FEATURES

- High speed sander
- Variable speed throttle
- Compact and lightweight
- Low vibration

BENEFITS

- Ideal for tight access work
- Precise control
- Easy handling
- Flexibility



See accessories on page 35

MODEL	PART NUMBER	FREE SPEED	PAD SIZE		SPINDLE THREAD	AIR CONSUMPTION		OVERALL LENGTH		NET WEIGHT		NOISE LEVEL	SOUND POWER	VIBRATION	AIR INLET
		rpm	mm	in.	in.	l/s	cfm	mm	in.	kg	lb	dB(A)	dB(A)	m/s ²	NPTF
RP9164	615 193 9164	9,600	152	6	5/16-24	8.80	18	222	8.75	1.7	3.8	90	101	7.3	1/4"
RP9534	615 193 9534	9,000	152	6	5/16-24	8.97	19	190	7.5	1.3	2.9	83	-	<2.5	1/4"
RP9674	615 193 9674	9,000	152	6	5/16-24	8.97	19	190	7.5	1.3	2.9	83	-	<2.5	1/4"
RP9778	615 193 9778	18,500	127	5	7/16-20	12.0	26	203	8.0	1.0	2.3	90	101	<2.5	1/4"

@90 PSI(@6.3 Bar) - Listed specifications are for reference only. Please check documents in each tool.